



Fleet

SAE 30, 40, 50
API: CF

Fleet Engine oil series are specially designed for comparatively old condition diesel engines. This oil is designed from high quality base oil with advanced additives package to provide better engine protection. It contains higher alkalinity to neutralize effect of deleterious combustion products associated with high Sulphur present in the fuel for diesel engine. This oil is equally suitable for all kinds of Heavy Duty Commercial Engines working in severe conditions.

BENEFITS

- Minimizes fuel and oil consumption.
- Protects engine from rust and corrosion.
- Ensures better oxidation and thermal stability.
- Ensures sludge control and wear protection at high temperature.



TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS		
		30	40	50
SAE VISCOSITY GRADE	-	30	40	50
Appearance	ASTM D 4176	B & C	B & C	B & C
Color	ASTM D 1500	L 2.0	L 2.5	L 2.5
Density at 30°C gm/ml	ASTM D 4052	0.884	0.886	0.887
Kinematic Viscosity @ 40°C	ASTM D 445	100.96	149.44	214.46
Kinematic Viscosity @ 100°C	ASTM D 445	11.94	15.23	18.65
Viscosity Index	ASTM D 2270	104	100	98
Flash Point °C	ASTM D 92	228	242	248
Pour Point °C	ASTM D 97	-15	-12	-12

Data Sheet



Furnishing the information contained herein does not constitute a representation by Sigma Oil Industries Limited that any product of process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Sigma Oil Industries Limited or any third party. Sigma Oil Industries Limited assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions to use and application presented herein represent the best information available to us and are believed to be reliable. They should not however be considered as controlling suggestions and users urged to conduct confirmatory test to determine final suitability for their specific end uses. Sigma Oil Industries Limited warrants only that its products meet the specification which is set for them and specially **DISCLAIMS ALL OTHER WARRANTIES** relating to the products and the application thereof **EXPRESS** or **IMPLIED** including but not limited to warranties of **MERCHANTABILITY** and **FLTNES**.

