

# Super Gear Oil

**SAE 80W90, 85W140**  
**API: GL-4**

**Super Gear Oil Series** is a super quality gear oil with quality base oil and balanced additives ingredients. This oil is designed for all types of gears used in extreme pressure. Special high-pressure agents and other additives of this oil offer excellent wear protection and oxidation stability. By Meeting the API GL-4 required specifications this oil meets most demanding requirements of gears.

## BENEFITS

- ❖ Good foam resistant.
- ❖ Ensures longer trouble-free protection.
- ❖ Excellent thermal and chemical stability.
- ❖ Highest protection against rust and corrosion.
- ❖ Compatible with all types of metals and sealing materials.



## TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS	
		80W90	85W140
SAE VISCOSITY GRADE	-	80W90	85W140
Appearance	ASTM D 4176	B & C	B & C
Color	ASTM D 1500	L 2.0	L 2.5
Density at 30°C gm/ml	ASTM D 4052	0.883	0.892
Kinematic Viscosity @ 40°C	ASTM D 445	190.63	429.85
Kinematic Viscosity @ 100°C	ASTM D 445	17.38	30.11
Viscosity Index	ASTM D 2270	98	99
Flash Point °C	ASTM D 92	228	255
Pour Point °C	ASTM D 97	-15	-15

Data Sheet

