



ATF

Automatic Transmission Fluid DEXRON-III H

ATF DEXRON-III H is made from **Hydrocracked** base oil with special additives package. It is the latest output of lubricating technology. It contains viscosity index improvers, anti-oxidants, anti-wear, detergents, extremely low pour point and improved low temperature fluidity. This fluid provides unique advantages in long term friction retention and air release properties.

APPLICATION

It is suitable for automatic transmissions in passenger cars and light duty trucks and power steering unit. It is also suitable for hydraulic systems in farm equipment and other installations having similar fluid requirements.

BENEFITS

- Keep gear clean.
- Better fuel economy.
- Excellent anti-wear and anti-rust properties.
- All year round usability.
- Low maintenance cost through better performance.



TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS
SAE VISCOSITY GRADE	-	-
Appearance	ASTM D 4176	B & C
Color	ASTM D 1500	Red
Density at 30°C gm/ml	ASTM D 4052	0.852
Kinematic Viscosity @ 40°C	ASTM D 445	44.71
Kinematic Viscosity @ 100°C	ASTM D 445	7.77
Viscosity Index	ASTM D 2270	140
Flash Point °C	ASTM D 92	212
Pour Point °C	ASTM D 97	-24

Data Sheet



Furnishing the information contained herein does not constitute a representation by Sigma Oil Industries Limited that any product of process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Sigma Oil Industries Limited or any third party. Sigma Oil Industries Limited assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions to use and application presented herein represent the best information available to us and are believed to be reliable. They should not however be considered as controlling suggestions and users urged to conduct confirmatory test to determine final suitability for their specific end usage. Sigma Oil Industries Limited warranties only that it's products meet the specification which is set for them and specially **DISCLAIMS ALL OTHER WARRANTIES** relating to the products and the application thereof **EXPRESS or IMPLIED** including but not limited to warranties of **MERCHANTABILITY** and **FITNESS**.

