



# Multi-Purpose Gear Oil

**SAE 80W90, 85W140  
GL-5**

Multi-Purpose Gear Oil series consist a range of extreme pressure and high-performance gear lubricants that deliver superior performance for both on-highway vehicles and off-highway farm and construction equipment. Being product of GL-5, this series excellently work over a wide range of temperatures and severe working conditions. The additives of this package contain superior thermal and oxidation properties that provide a greater temperature protection over a time. In addition, extreme pressure additives provide optimum protection against shock loading and offer highest loading capabilities.

This series are widely recommended to all of industrial settings.

## APPLICATION

Suitable for use in different gear boxes, differentials, pinions, axles, final drives and manual transmissions. Also compatible for hypoid and bevel gear differentials.

## BENEFITS

- Non corrosive properties.
- Outstanding rust and corrosion protection.
- Good resistance to foaming that reduces oxidation and fluid breakdown.
- EP properties reduce wear in heavily loaded gear sets.
- Excellent oxidation stability reduces oil degradation.



Data Sheet



Furnishing the information contained herein does not constitute a representation by Sigma Oil Industries Limited that any product of process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Sigma Oil Industrues Limited or any third party. Sigma Oil Industries Limited assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions to use and application presented herein represent the best information available to us and are belived to be reliable. They should not however be considered as controlling suggestions and users urged to conduct confirmatory test to determine final suitability for their specific end usage. Sigma Oil Industries Limited warranties only that it's products meet the specification which is set for them and specially **DISCLAIMS ALL OTHER WARRANTIES** relating to the products and the application thereof **EXPRESS or IMPLIED** including but not limited to warranties of **MERCHANTABILITY and FITNESS**.





# Multi-Purpose Gear Oil

SAE 80W90, 85W140  
GL-5

## TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS	
		80W90	85W140
SAE VISCOSITY GRADE	-	80W90	85W140
Appearance	Visual	B&C	B & C
Color	ASTM D 1500	L 2.0	L 2.5
Density at 30°C	ASTM D 4052	0.8832	0.899
Kinematic Viscosity @ 40°C	ASTM D 445	181.66	458.17
Kinematic Viscosity @ 100°C	ASTM D 445	17.57	30.36
Viscosity Index (VI)	ASTM D 2270	105	95
Pour Point (PP)	ASTM D 97	-15	-12
Flash Point (FP)	ASTM D 92	225	221

Data Sheet

# SOIL



Furnishing the information contained herein does not constitute a representation by Sigma Oil Industries Limited that any product of process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Sigma Oil Industries Limited or any third party. Sigma Oil Industries Limited assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions to use and application presented herein represent the best information available to us and are believed to be reliable. They should not however be considered as controlling suggestions and users urged to conduct confirmatory test to determine final suitability for their specific end usage. Sigma Oil Industries Limited warrants only that its products meet the specification which is set for them and specially **DISCLAIMS ALL OTHER WARRANTIES** relating to the products and the application thereof **EXPRESS** or **IMPLIED** including but not limited to warranties of **MERCHANTABILITY** and **FITNESS**.

