



## Sigma Active

SAE 30, 40, 50, 60 API SC/CC

**Active Series 30, 40, 50, 60** are mono - grade engine oil formulated from excellent quality base stocks with superior additives package. It is especially suitable for gasoline and diesel engines of Agricultural sector. By meeting the API standard specification, it provides excellent engine protection, superior thermal stability with the quality of anti-wear and detergency.

## **BENEFITS**

- Provides highest engine protection.
- Prolongs drain interval.
- Ensures minimum maintenance cost.
- Ensures smooth engine operation.

## TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS			
GRADE		SAE 30	SAE 40	SAE 50	SAE 60
ASTM Color	ASTM D 1500	L 2.5	L 2.5	L 2.5	L 2.5
Density at 30°C gm/ml	ASTM D 4052	0.878	0.8811	0.8844	0.889
Kinematic Viscosity at 40°C	ASTM D 445	103.17	149.44	214.46	300.56
Kinematic Viscosity at 100°C	ASTM D 445	11.45	14.95	18.83	23.75
Viscosity Index	ASTM D 2270	97	100	98	99
Pour Point	ASTM D 97	-12	-12	-15	-12
Flash Point	ASTM D 92	240	245	270	238
TBN	ASTM D 5984	4.10	6.18	4.2	4.1



