

## Exceed

SAE 20W50 API: SL/CF

**Exceed** SAE 20W50 API SL/CF is a premium quality lubricants designed for gasoline, diesel, LPG and CNG driven vehicles work under severe conditions. This product is formulated from high quality base stocks with advanced additives package. By meeting the API performance of SL/CF Sigma Exceed 20W50 exceeds most demanding requirements in relation to emission control, oil consumption, volatility and thermal stability.

## **BENEFITS**

- Minimizes fuel and oil consumption.
- Provides Oxidation and thermal stability.
- Protects engines from deposit and exhaust blocking.
- Ensures smooth operation of all high performance engines.

## **TYPICAL CHARACTERISTICS**

TEST DESCRIPTION	METHOD	TYPICAL RESULTS
SAE VISCOSITY GRADE	-	20W50
Appearance	ASTM D 4176	B & C
Color	ASTM D 1500	L 3.0
Density at 30°C gm/ml	ASTM D 4052	0.875
Kinematic Viscosity @ 40°C	ASTM D 445	166.67
Kinematic Viscosity @ 100°C	ASTM D 445	19.05
Viscosity Index	ASTM D 2270	130
TBN	ASTM D 2896	6.9
Flash Point °C	ASTM D 92	235
Pour Point °C	ASTM D 97	-15





