



ULTRA PRO

FULLY SYNTHETIC

SAE 5W30 API SP ILSAC GF-6

PRODUCT DESCRIPTION

SOIL Ultra Pro synthetic engine oil which made with high performance synthetic base oil and special additive technology that provides excellent engine cleanliness, wear protection at high temperatures and protection against corrosion. This highly reliable oil helps to maintain optimum engine output and improves responsiveness.

KEY FEATURES

- Synthetic formulation maximizes power and acceleration
- Help to provide engine cleanliness, smooth and reliable operation
- Added protection against harmful deposits formation
- Excellent wear protection to keep engine performing at its best
- Affordable solution to extending your oil drain intervals.



APPLICATION

This synthetic oil is recommended for gasoline and diesel passenger cars. Also suitable for engines operating in extreme conditions. For use in most domestic and import conventional and hybrid passenger cars. It can meet the oil demand of high speed four stroke naturally aspirated turbocharged diesel engines.

TYPICAL PROPERTIES

| PARAMETERS | ASTM METHOD | RESULTS |
|------------------------------|-------------|---------|
| Appearance | Visual | B&C |
| ASTM Color | ASTM D-1500 | L 3.0 |
| Density at 15oC | ASTM D-4052 | 0.8372 |
| Density at 30oC | ASTM D-4052 | 0.8281 |
| Kinematic Viscosity at 40oC | ASTM D-7042 | 67.36 |
| Kinematic Viscosity at 100oC | ASTM D-7042 | 11.96 |
| Viscosity Index (VI) | ASTM D-2270 | 176 |
| Total Base Number (TBN) | ASTM D-2896 | 5.9 |
| Flash Point (FP) | ASTM D-92 | 225 |
| Pour Point (PP) | ASTM D-97 | -32 |



Furnishing the information contained herein does not constitute a representation by Sigma Oil Industries Limited that any product of process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Sigma Oil Industries Limited or any third party. Sigma Oil Industries Limited assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions to use and application presented herein represent the best information available to us and are believed to be reliable. They should not however be considered as controlling suggestions and users urged to conduct confirmatory test to determine final suitability for their specific end usage. Sigma Oil Industries Limited warrants only that its products meet the specification which is set for them and specially DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof EXPRESS or IMPLIED including but not limited to warranties of MERCHANTABILITY and FITNESS.

Sheet Data