

BRAKE FLUID DOT 3

Brake Fluid DOT 3 is a high-performance polyglycol type Brake Fluid designed to use in brake and clutch systems. It optimizes the benefits of superior boiling point and high vapor lock temperature through its service life.

Brake Fluid DOT 3 is compatible with all metals and rubber seals typically used in automotive braking systems. It is suitable for disc, drum and anti-skid ABS braking and electronic stability control systems used in high performance vehicles with high thermal load around the braking systems.

BENEFITS

- ◆ Formulated from polyglycol with lubricity additives and corrosion inhibitors.
- ◆ High level system protection.
- ◆ Excellent lubricating properties.
- ◆ Correct fluidity and kinematics viscosity.
- ◆ Proper anti-oxidants, metal deactivator and
- ◆ corrosion inhibitors.



TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS
SAE VISCOSITY GRADE	-	-
Appearance	Visual	B & C
pH	SAE J1703	7-11
Density at 20°C	ASTM D 4052	1.09
Equilibrium Reflux Boiling Point °C	SAE J1703	Min 245
Equilibrium Reflux Boiling Point °C	SAE J1703	Min 150
Kinematic Viscosity at 100°C	FMVSS 116 (3)	2.2

