

# Power HD

**SAE 30, 40, 50, 60**  
**API SC/CC**

Power HD is mono-grade engine oil formulated from excellent quality base stocks with superior additives package. It is suitable for gasoline and diesel engines as well as farm equipments.

By meeting the API standard specification it provides excellent engine protection, superior thermal stability with the quality of anti wear and detergency.

## BENEFITS

- Prolongs drain interval.
- Ensures smooth engine operation.
- Provides highest engine protection.
- Ensures minimum maintenance cost.



## TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS			
		30	40	50	60
SAE VISCOSITY GRADE	-	30	40	50	60
Appearance	ASTM D 4176	B & C	B & C	B & C	B & C
Color	ASTM D 1500	L 2.0	L 2.5	L 2.5	L 3.0
Density at 30°C gm/ml	ASTM D 4052	0.878	0.881	0.884	0.889
Kinematic Viscosity @ 40°C	ASTM D 445	103.17	149.44	214.46	300.56
Kinematic Viscosity @ 100°C	ASTM D 445	11.45	14.95	18.83	23.75
Viscosity Index	ASTM D 2270	97	100	98	99
TBN	ASTM D 2896	4.1	6.18	4.1	4.1
Flash Point °C	ASTM D 92	240	241	270	238
Pour Point °C	ASTM D 97	-12	-12	-15	-12

Data Sheet

