



# 4T Plus

**SAE 20W40**

**API: SF/CD**

**Naf Arab 4T Plus** Motorcycle oil is premium quality 4 stroke engine oil specially designed for motorcycles. This oil is manufactured under the advanced formulation with top quality base oil with proper additives. Its high additives content help to protect engines and extend drain period. The specification of this oil meets the requirements of all worldwide engine makers for tropical weather.

## BENEFITS

- Prolongs drain interval.
- Ensures smooth engine operation.
- Provides highest engine protection.
- Ensures minimum maintenance cost.



## TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS
SAE VISCOSITY GRADE	-	<b>20W40</b>
Appearance	ASTM D 4176	B & C
Color	ASTM D 1500	L 2.5
Density at 30°C gm/ml	ASTM D 4052	0.868
Kinematic Viscosity @ 40°C	ASTM D 445	127.8
Kinematic Viscosity @ 100°C	ASTM D 445	15.53
Viscosity Index	ASTM D 2270	128
TBN	ASTM D 2896	4.3
Flash Point °C	ASTM D 92	238
Pour Point °C	ASTM D 97	-15

Data Sheet



Furnishing the information contained herein does not constitute a representation by Sigma Oil Industries Limited that any product of process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Sigma Oil Industries Limited or any third party. Sigma Oil Industries Limited assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions to use and application presented herein represent the best information available to us and are believed to be reliable. They should not however be considered as controlling suggestions and users urged to conduct confirmatory test to determine final suitability for their specific end uses. Sigma Oil Industries Limited warrants only that its products meet the specification which is set for them and specially **DISCLAIMS ALL OTHER WARRANTIES** relating to the products and the application thereof **EXPRESS or IMPLIED** including but not limited to warranties of **MERCHANTABILITY** and **FLTNES**.

