

# Power

**SAE 20W50**

**API: SF/CD**

**Power** is high performance multi-grade engine oil designed to use in gasoline automotive engines of passenger cars, commercial vehicles and 4-Stroke motorcycles. This oil is formulated from high quality base oil with advanced additives package to provide excellent performance required for modern combust engines. It can also be used in diesel engines of commercial vehicles. By meeting the API performance level it satisfies most demanding requirement of modern engines.

## BENEFITS

- Ensures long drain intervals.
- Resists oxidation and foaming.
- Minimizes fuel and oil consumption.
- Protects engines from wear and corrosion.



## TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS
<b>SAE VISCOSITY GRADE</b>	-	<b>20W50</b>
Appearance	ASTM D 4176	B & C
Color	ASTM D 1500	L 2.5
Density at 30°C gm/ml	ASTM D 4052	0.878
Kinematic Viscosity @ 40°C	ASTM D 445	169.22
Kinematic Viscosity @ 100°C	ASTM D 445	18.94
Viscosity Index	ASTM D 2270	128
TBN	ASTM D 2896	5.6
Flash Point °C	ASTM D 92	240
Pour Point °C	ASTM D 97	-18

Data Sheet

