



Super 4T

SAE 10W30, 10W40, 20W40, 20W50

API SL, JASO MA-2

Super 4T is a Hydrocrack base multi grade motorcycle engine oil uniting the latest developed technologies and advanced additives Package. By meeting the required API performance level, Super 4T exceeds most demanding requirement related to engine system such as emission control, oil consumption and volatility.

It gives outstanding performance in all type of Japanese, American, European and Indian 4-strokes motorcycles, Private cars and other petrol, CNG/LPG driven 4-strokes engines.

APPLICATION

Exceed the recommends of most car manufacturer including **Yamaha, Suzuki, Honda, Bajaj, TVS, Hero, Runner, Mahindra** and others.

BENEFITS

- Extends engine life.
- Keeps engine clean.
- Minimizes oil consumption.
- Protects gear box and clutch.
- Smoothens Sound.
- Protects Rust and Oxidation.



TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS			
SAE VISCOSITY GRADE	-	10W30	10W40	20W40	20W50
Appearance	ASTM D 4176	B & C	B & C	B & C	B & C
Color	ASTM D 1500	L 2.0	L 2.5	L 2.0	L 3.0
Density at 30°C gm/ml	ASTM D 4052	0.843	0.860	0.861	0.865
Kinematic Viscosity @ 40°C	ASTM D 445	70.35	116.21	117.4	165.63
Kinematic Viscosity @ 100°C	ASTM D 445	11.43	15.09	15.32	18.67
Viscosity Index	ASTM D 2270	156	135	138	127
TBN	ASTM D 2896	6.5	6.5	6.5	6.5
Flash Point °C	ASTM D 92	225	227	225	255
Pour Point °C	ASTM D 97	-18	-18	-18	-18

Data Sheet



Furnishing the information contained herein does not constitute a representation by Sigma Oil Industries Limited that any product of process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Sigma Oil Industries Limited or any third party. Sigma Oil Industries Limited assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions to use and application presented herein represent the best information available to us and are believed to be reliable. They should not however be considered as controlling suggestions and users urged to conduct confirmatory test to determine final suitability for their specific end usage. Sigma Oil Industries Limited warranties only that it's products meet the specification which is set for them and specially **DISCLAIMS ALL OTHER WARRANTIES** relating to the products and the application thereof **EXPRESS or IMPLIED** including but not limited to warranties of **MERCHANTABILITY and FITNESS**.

