



SUPER 4T

SAE 10W30, 10W40, 20W40, 20W50 API SM, JASO MA-2

Supra 4T is a **Synthetic Blend** multi grade motorcycle engine oil uniting the latest developed motorcycle technologies and advanced additives Package.

This oil is ultimate solution to all types of Japanese, American, European and Indian 4-strokes motorcycles, Private cars and other petrol, CNG/LPG driven 4-strokes engines.

APPLICATION

Exceed the recommends of most car manufacturer including Yamaha, Suzuki, Honda, Bajaj, TVS, Hero, Runner, Mahindra and others.

BENEFITS

- Protect gear box and clutch.
- Keep engine clean.
- Protect rust and oxidation.
- Give engine life.

TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS			
SAE VISCOSITY GRADE	-	10W30	10W40	20W40	20W50
Appearance	ASTM D 4176	B & C	B & C	B & C	B & C
Color	ASTM D 1500	L 1.5	L 2.0	L 2.0	L 2.5
Density at 30°C gm/ml	ASTM D 4052	0.842	0.859	0.857	0.847
Kinematic Viscosity @ 40°C	ASTM D 445	69.56	102.38	103	170.85
Kinematic Viscosity @ 100°C	ASTM D 445	12.02	15.34	14.4	18.52
Viscosity Index	ASTM D 2270	171	135	132	125
TBN	ASTM D 2896	7.5	7.5	7.5	232
Flash Point °C	ASTM D 92	220	227	228	222
Pour Point °C	ASTM D 97	-24	-22	-20	-20



