



# Supreme 4T

## Fully Synthetic Motorcycle Oil SAE 5W30, SAE 5W40 API SN JASO MA-2

**Supreme 4T** is a **Fully Synthetic** higest API Racing motorcycle oil. This oil is made with high performance synthetic base oil and special additive technology which provides excellent engine cleanliness, wear protection at high temperatures and protection against corrosion. This highly reliable oil helps to maintain optimum power output and smoother gear shifting and improves responsiveness. It is recommended for four-stroke motorcycles and ATV's.

## **KEY FEATURES**

- Synthetic formulation maximizes power and acceleration.
- Help to provide engine cleanliness, smooth and reliable operation.
- Added protection against harmful deposits formation.
- Excellent wear protection to keep engine performing at its best.
- Affordable solution to extending your oil drain intervals.
- Outstanding wet-clutch protection for maximum power and smooth gear shifting.



#### **APPLICATION**

This Fully Synthetic oil is recommended for motorcycle engines operating in extreme conditions. It has outstanding soot control for protection against abrasive wear and soot-induced oil thickening.

### **TYPICAL CHARACTERISTICS**

TEST DESCRIPTION	METHOD	TYPICAL RESULTS	
SAE VISCOSITY GRADE	-	5W30	5W40
Appearance	ASTM D 4176	B & C	B & C
Color	ASTM D 1500	L 2.5	L 2.5
Density at 30°C gm/ml	ASTM D 4052	0.843	0.847
Kinematic Viscosity @ 40°C	ASTM D 445	69.8	102.3
Kinematic Viscosity @ 100°C	ASTM D 445	12.1	15.31
Viscosity Index	ASTM D 2270	170	158
TBN	ASTM D 2896	7.5	7.5
Flash Point °C	ASTM D 92	225	228
Pour Point °C	ASTM D 97	-20	-20



Furnishing the information contained herein does not constitute a representation by Sigma Oil Industries Limited that any product of process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Sigma Oil Industries Limited or any third party. Sigma Oil Industries Limited assumes no liability for any infringment which might arise out of the use of the product. The information and suggestions to use and application presented herein represent the best information available to us and are belived to be reliable. They should not however be considered as controling suggestions and users urged to conduct confirmatory test to determine final suitability for their specific end usage. Sigma Oil Industries Limited warranties only that it's products meet the specification which is set for them and specially DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof EXPRESS or IMPLIED including but not limited to warranties of MERCHANTABILITY and FITNESS.

