



ULTRA 4T

Maximum Technology Engine Oil

SAE 10W30, 10W40, 20W40, 20W50

API SL, JASO MA

ULTRA 4T is a newly introduced premium quality lube oil for 4-strokes motorcycles. It is specially formulated to provide outstanding protection against friction and wear for both engine and transmission. It has absolutely good shear stability, keeping motorcycles well-protected even in extreme heat conditions. This product is specially designed for both air and liquid cooled engines. It meets API SL, JASO MA specifications.

APPLICATION

Exceed the recommends of most bike manufacturers including Yamaha, Suzuki, Honda, Bajaj, TVS, Hero, Runner, Mahindra and others.

BENEFITS

- * Give excellent engine cleanliness.
- * Delivers excellent wear protection.
- * Provides optimum friction and heat.
- * Prevents sludge and carbon deposits.
- * Delivers smooth gear and clutch performance.



TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS			
SAE VISCOSITY GRADE	-	10W30	10W40	20W40	20W50
Appearance	ASTM D 4176	B & C	B & C	B & C	B & C
Color	ASTM D 1500	L 2.0	L 2.5	L 2.5	3
Density at 30°C gm/ml	ASTM D 4052	0.844	0.860	0.861	0.865
Kinematic Viscosity @ 40°C	ASTM D 445	71.23	115.31	116	164.34
Kinematic Viscosity @ 100°C	ASTM D 445	11.5	15.08	15.1	18.25
Viscosity Index	ASTM D 2270	152	135	135	128
TBN	ASTM D 2896	7.1	7.1	7.1	7.1
Flash Point °C	ASTM D 92	227	222	223	252
Pour Point °C	ASTM D 97	-18	-18	-18	-18



Furnishing the information contained herein does not constitute a representation by Sigma Oil Industries Limited that any product of process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Sigma Oil Industries Limited or any third party. Sigma Oil Industries Limited assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions to use and application presented herein represent the best information available to us and are believed to be reliable. They should not however be considered as controlling suggestions and users urged to conduct confirmatory test to determine final suitability for their specific end usage. Sigma Oil Industries Limited warrants only that its products meet the specification which is set for them and specially DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof EXPRESS or IMPLIED including but not limited to warranties of MERCHANTABILITY and FITNESS.



Data Sheet