



# CVT FLUID - TC

## DESCRIPTION

**SOIL CVT Fluid** is a premium quality fully synthetic transmission fluid specially designed for passenger car with belt driven continuously variable transmission. It has been specially engineered to have the unique fractional properties required for use in this type of transmission.

## APPLICATION

It is suitable for automatic transmissions in passenger cars and light duty trucks and power steering unit. It is also suitable for hydraulic systems in farm equipment and other installations having similar fluid requirements. Excellent low temperature properties for easier shifting in cold weather.

## BENEFITS

- Excellent oxidation resistance and thermal stability for long fluid life.
- Meets performance requirements for nearly all vehicles with belt type continuously variables transmission.
- Protects against sludge and varnish formation.
- Protects against wear, rust and corrosion.
- Good seal compatibility and foam resistance.

## TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS
<b>SAE VISCOSITY GRADE</b>	-	-
Appearance	ASTM D 4176	B & C
Color	ASTM D 1500	Red
Density at 30°C gm/ml	ASTM D 4052	0.853
Kinematic Viscosity @ 40°C	ASTM D 445	34.7
Kinematic Viscosity @ 100°C	ASTM D 445	7.2
Viscosity Index	ASTM D 2270	186
Flash Point °C	ASTM D 92	204
Pour Point °C	ASTM D 97	-45

Data Sheet



Furnishing the information contained herein does not constitute a representation by Sigma Oil Industries Limited that any product of process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Sigma Oil Industries Limited or any third party. Sigma Oil Industries Limited assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions to use and application presented herein represent the best information available to us and are believed to be reliable. They should not however be considered as controlling suggestions and users urged to conduct confirmatory test to determine final suitability for their specific end usage. Sigma Oil Industries Limited warrants only that it's products meet the specification which is set for them and specially **DISCLAIMS ALL OTHER WARRANTIES** relating to the products and the application thereof **EXPRESS** or **IMPLIED** including but not limited to warranties of **MERCHANTABILITY** and **FITNESS**.

