

Super Fleet

SAE 15W40
API: CI-4/SL

Super Fleet is a high-quality multi-grade engine oil blended from quality base oil with advance technology additives package to provide better engine protection. It is especially designed to use in all kinds of new condition Heavy Duty Commercial Engines whatever the working conditions. By meeting the API CI-4/SL performance level Super Fleet meets the requirements of major global engine manufactures.

BENEFITS

- ◆ Minimizes oil consumption.
- ◆ Protects engines against wear and dust.
- ◆ Meets most diesel engines OEM Specifications.
- ◆ Suitable for the modern diesel engines equipped with EGR.



TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS
SAE VISCOSITY GRADE	-	15W40
Appearance	ASTM D 4176	B & C
Color	ASTM D 1500	L 3.0
Density at 30°C gm/ml	ASTM D 4052	0.861
Kinematic Viscosity @ 40°C	ASTM D 445	106.98
Kinematic Viscosity @ 100°C	ASTM D 445	14.83
Viscosity Index	ASTM D 2270	144
TBN	ASTM D 2896	9.9
Flash Point °C	ASTM D 92	222
Pour Point °C	ASTM D 97	-18

Data Sheet

