

Turbo Fleet *Supreme*

SAE 15W40
API: CI-4/SL

Turbo Fleet Supreme is a high quality multi-grade engine oil blended from quality base oil with advance technology additives package to provide better engine protection. This superior performance multi-grade engine oil is designed to use in most of the Indian, American, European and Japanese Heavy duty diesel engine manufacturers. It is recommended for high speed, turbo charged 4-stroke engines particularly equipped with emission design engines.

BENEFITS

- Minimizes oil consumption.
- Protects engines against wear and dust.
- Meets most diesel engines OEM Specifications.
- Suitable for the modern diesel engines equipped with EGR.



TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS
SAE VISCOSITY GRADE	-	15W40
Appearance	ASTM D 4176	B & C
Color	ASTM D 1500	L 3.0
Density at 30°C gm/ml	ASTM D 4052	0.861
Kinematic Viscosity @ 40°C	ASTM D 445	106.98
Kinematic Viscosity @ 100°C	ASTM D 445	14.83
Viscosity Index	ASTM D 2270	144
TBN	ASTM D 2896	9.9
Flash Point °C	ASTM D 92	222
Pour Point °C	ASTM D 97	-18

Data Sheet

