



Ornate Max-1000

Heavy Duty Diesel Engine Oil

SAE 20W50, API:CI-4/SL

Ornate Max-1000 is super quality diesel engine oil blended with special quality hydrocracked base fluid and premium additives. As it contains the anti-oxidant property at a great extend with premium additives and technology, it can reduce the carbon created at today's highly operating temperature. It reduces the oil consumption and extends the drain-interval much longer than that of conventional mineral base engine oil. It gives outstanding performance in all type of Japanese, European, American and Indian latest as well as old-model vehicles for all weathers.

Ornate Max-1000 exceeds API CI-4 / SL standard and meets most of the European Diesel Engine OEM requirements.

APPLICATION

Ornate Max-1000 is recommended for use in heavily loaded diesel engines in commercial use and heavy-duty diesel engine used in construction, mining and quarrying. It is equally applicable both for old and new engine.

BENEFITS

- All year-round usability.
- Highest engine protection.
- Very long drain intervals.
- Minimizes oil consumption.
- Anti-wear & anti-oxidant.
- Advanced premium quality oil with Synthetic Technology.
- Optimizes friction in the clutch and reduces internal engine losses due to friction.

TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS
SAE VISCOSITY GRADE	-	20W50
Appearance	ASTD D 4176	B & C
Color	ASTM D 1500	L 3.5
Density at 30°C gm/ml	ASTM D 4052	0.872
Kinematic Viscosity @ 40°C	ASTM D 445	146.7
Kinematic Viscosity @ 100°C	ASTM D 445	18.6
Viscosity Index	ASTM D 2270	143
TBN	ASTM D 5984	13.5
Flash Point °C	ASTM D 92	223
Pour Point °C	ASTM D 97	-20



Furnishing the information contained herein does not constitute a representation by Sigma Oil Industries Limited that any product of process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Sigma Oil Industries Limited or any third party. Sigma Oil Industries Limited assumes no liability for any infringment which might arise out of the use of the product. The information and suggestions to use and application presented herein represent the best information available to us and are belived to be reliable. They should not however be considered as controling suggestions and users urged to conduct confirmatory test to determine final suitability for their specific end usage. Sigma Oil Industries Limited warranties only that it's products meet the specification which is set for them and specially DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof EXPRESS or IMPLIED including but not limited to warranties of MERCHANTABILITY and FITNESS.





SOIL





Ornate Max-1000

PERFORMANCE STANDARDS

- API: CI-4 / SL
- MB 229.1
- MB 228.1 /228.3
- ZF TE-ML07C
- ZF TE-ML04C
- Allison C-4
- VOLVO VDS-3
- Detroit Diesel DDC 93K214
- ACEA 2004 E7-04
- ACEA 1996 E2-05
- ACEA 1998 B3-02
- ACEA 1996 A2-03
- MTU Oil Category 1
- Caterpillar ECF 1
- MAN 271
- Cummins CES 20078
- Mack EO-M Plus
- Mack EO-N Premium plus 03







