



# Zoom

*World Class Engine Oil*

**SAE 20W-50**

**API SL /CF-4**

**Zoom** is a specially formulated super grade gasoline lubricant for all types of passenger cars, vans and light duty trucks under extremely severe driving condition all through the year. This oil is blended from high quality hydrocracked base oil incorporated with effective additives. It is designed to meet the most severe requirements of modern high performance engines. It contains superior quality detergent/dispersants, anti-oxidation, anti wear and anti-corrosion properties.

Special attention is given to quality reserve to keep the engine safe even with extended oil drains. It contains superior stable viscosity index improver that doesn't shear under severe operating conditions of high load and elevated temperature.

This oil is recommended to use in all types of Diesel, Petrol, Octane, CNG, LPG engines where conventional motor oils are recommended. This oil is enriched with a special additives that made it fit for the best performance in any types of 4 stokes motorcycles also.

## BENEFITS

- All year round usability.
- Excellent oxidation protection.
- Minimizes varnish and sludge.
- Sweet strawberry fragrance with dyed in Red.
- Provides excellent protection against engine wear.
- High level of detergent/dispersant keeps engine clean.
- Remarkable low oil consumption and better fuel economy.



## TYPICAL CHARACTERISTICS

| TEST DESCRIPTION            | METHOD      | TYPICAL RESULTS |
|-----------------------------|-------------|-----------------|
| <b>SAE VISCOSITY GRADE</b>  | -           | <b>20W50</b>    |
| Appearance                  | ASTM D 4176 | B & C           |
| Color                       | ASTM D 1500 | Red             |
| Density at 30°C gm/ml       | ASTM D 4052 | 0.865           |
| Kinematic Viscosity @ 40°C  | ASTM D 445  | 142.7           |
| Kinematic Viscosity @ 100°C | ASTM D 445  | 17.2            |
| Viscosity Index             | ASTM D 2270 | 131             |
| TBN                         | ASTM D 2896 | 7.1             |
| Flash Point °C              | ASTM D 92   | 235             |
| Pour Point °C               | ASTM D 97   | -21             |

Data Sheet



Furnishing the information contained herein does not constitute a representation by Sigma Oil Industries Limited that any product of process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Sigma Oil Industries Limited or any third party. Sigma Oil Industries Limited assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions to use and application presented herein represent the best information available to us and are believed to be reliable. They should not however be considered as controlling suggestions and users urged to conduct confirmatory test to determine final suitability for their specific end usage. Sigma Oil Industries Limited warranties only that it's products meet the specification which is set for them and specially **DISCLAIMS ALL OTHER WARRANTIES** relating to the products and the application thereof **EXPRESS or IMPLIED** including but not limited to warranties of **MERCHANTABILITY and FITNESS**.

