

Fleet

SAE 30, 40, 50
API: CF

Fleet Engine oil series are specially designed for comparatively old condition diesel engines. This oil is designed from high quality base oil with advanced additives package to provide better engine protection. It contains higher alkalinity to neutralize effect of deleterious combustion products associated with high Sulphur present in the fuel for diesel engine. This oil is equally suitable for all kinds of Heavy Duty Commercial Engines working in severe conditions.

BENEFITS

- Minimizes fuel and oil consumption.
- Protects engine from rust and corrosion.
- Ensures better oxidation and thermal stability.
- Ensures sludge control and wear protection at high temperature.



TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS		
		30	40	50
SAE VISCOSITY GRADE	-	30	40	50
Appearance	ASTM D 4176	B & C	B & C	B & C
Color	ASTM D 1500	L 2.0	L 2.5	L 2.5
Density at 30°C gm/ml	ASTM D 4052	0.884	0.886	0.887
Kinematic Viscosity @ 40°C	ASTM D 445	100.96	149.44	214.46
Kinematic Viscosity @ 100°C	ASTM D 445	11.94	15.23	18.65
Viscosity Index	ASTM D 2270	104	100	98
Flash Point °C	ASTM D 92	228	242	248
Pour Point °C	ASTM D 97	-15	-12	-12

