

# Supra

## SAE 40, 50 API: SF/CD

**Sigma Supra** is a super quality engine oil formulated from selected base fluids and additives package that is suitable for both gasoline and diesel powered vehicles and any others application. It contains highly effective dispersant inhibitor that controls sludge and other contaminants generated during stop and go or short trip delivery conditions. It is optimized to provide complete engine protection.

### APPLICATION

- Naturally aspirated and turbocharged gasoline passenger cars.
- Light truck gasoline engine
- Gas-fueled (CNG, LPG) 4 - Strokes gasoline engine.

### BENEFITS

- Low maintenance cost.
- Long engine life.
- High thermal stability for high temperature turbo protection.
- Minimizes varnish and sludge.
- Longer oil change interval.



### TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS	
		SAE 40	SAE 50
SAE VISCOSITY GRADE	-	SAE 40	SAE 50
ASTM Color	ASTM D 1500	L 2.0	L 2.5
Specific Gravity at 15°	ASTM D 1298	0.893	0.8889
Viscosity at 40°	ASTM D 445	161.33	189.23
Viscosity at 100°	ASTM D 445	15.41	18.56
Viscosity Index	ASTM D 2270	96	105
Pour Point	ASTM D 97	238	265
Flash Point	ASTM D 92	-12	-9
TBN	ASTM D 5984	5.79	4.21

### TYPICAL CHARACTERISTICS

- API: SF/CD

