

UNIQUE 4T

**SAE 20W50
API SL/CF, JASO MA**

UNIQUE 4T is a mineral base multi grade motorcycle engine oil uniting the latest developed technologies and advanced additives Package. By meeting the API SL/CF, JASO MA performance level, **UNIQUE 4T** exceeds most demanding requirement related to engine system such as emission control, oil consumption and volatility.

It gives outstanding performance in all type of Japanese, American, European and Indian 4-strokes motorcycles, Private cars and other petrol, CNG/LPG driven 4-strokes engines.

APPLICATION

Exceed the recommends of most car manufacturer including Yamaha, Suzuki, Honda, Bajaj, TVS, Hero, Runner, Mahindra and others.

BENEFITS

- Extends engine life.
- Keeps engine clean.
- Minimizes oil consumption.
- Protects gear box and clutch.
- Meets the requirements of API performance.
- Protects Rust and Oxidation.



TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS			
		10W30	10W40	20W40	20W50
SAE VISCOSITY GRADE	-	10W30	10W40	20W40	20W50
Appearance	ASTM D 4176	B & C	B & C	B & C	B & C
Color	ASTM D 1500	L 2.0	L 2.5		L 3.0
Density at 30°C gm/ml	ASTM D 4052	0.843	0.860		0.865
Kinematic Viscosity @ 40°C	ASTM D 445	70.35	116.21		165.63
Kinematic Viscosity @ 100°C	ASTM D 445	11.43	15.09		18.67
Viscosity Index	ASTM D 2270	156	135		127
TBN	ASTM D 2896				
Flash Point °C	ASTM D 92	225	227		255
Pour Point °C	ASTM D 97	-18	-18		-18

