



GGO - 626

SAE 40

GGO 626 is a super quality SAE 40 gas engine oil. It is produced from world class hydrocrack base oil with carefully chosen additives package. In addition, it contains low-ash, anti-wear and detergents additives that offers robust component protection even under heavy loads. As it keeps oxidation resistant and thermal stability properties properly, it gives outstanding performance in all operating conditions.

APPLICATION

This oil is used in natural gas fueled engines. It is highly effective to keep the Engine clean, long spark plug life and low sludge deposits. It is specially designed for spark ignition gas engines and also suitable for pilot ignition or dual type gas engines. It is equally suitable both for turbo charged or naturally aspirated gas engines.

BENEFITS

- Better fuel economy.
- Low maintenance cost though better performance.
- Keeps engine clean.
- All year-round usability.
- Excellent anti-corrosion properties.
- Longer spark plug life.
- Excellent break-in protection for high BMEP engines.
- Improves ring, piston and liner life.
- Less engine sludging.
- Reduces engine deposits.
- Reduces valve and combustion chamber ash and carbon build-up.



Data Sheet



Furnishing the information contained herein does not constitute a representation by Sigma Oil Industries Limited that any product of process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Sigma Oil Industries Limited or any third party. Sigma Oil Industries Limited assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions to use and application presented herein represent the best information available to us and are believed to be reliable. They should not however be considered as controlling suggestions and users urged to conduct confirmatory test to determine final suitability for their specific end usage. Sigma Oil Industries Limited warranties only that it's products meet the specification which is set for them and specially **DISCLAIMS ALL OTHER WARRANTIES** relating to the products and the application thereof **EXPRESS or IMPLIED** including but not limited to warranties of **MERCHANTABILITY and FITNESS**.





GGO - 626

SAE 40

TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS
SAE VISCOSITY GRADE		SAE 40
Appearance	ASTM D 4176	B & C
Color	ASTM D 1500	L 2.5
Density at 30°C gm/ml	ASTM D 4052	0.868
Kinematic Viscosity @ 40°C	ASTM D 445	146.48
Kinematic Viscosity @ 100°C	ASTM D 445	15.61
Viscosity Index	ASTM D 2270	110
Sulphated Ash (%wt)	ASTM D 874	0.3
TBN	ASTM D 2896	5.3
Flash Point °C	ASTM D 92	238
Pour Point °C	ASTM D 97	-18

PERFORMANCE STANDARDS

- Cummins: QSV 81G/91G, OSK 60G
- Guascor: FGLD, SFGLD
- MAN: 3271-2
- MTU: MLT 5074, A001061/29E (Category 1), Onsite Energy Series 400 and 4000
- MWM: TR 0199-99-2105
- MDE: Naturally Aspirated 28xx, 30xx, (D/M), Turbocharged 28xx, 30xx (T/L/Z)
- MAK: GCM 34
- Rolls Royce : KG-1, KG-2, KG-3, KD-4, BV-G
- Tedom: Natural Gas Engines
- Wartsila: 34SG, 32DF, 50DF, 25SG, 28SG, 175SG, 220SG
- Waukesha: Cogen and 220 GL (Pipeline Quality Natural Gas)
- Meets requirements of: Caterpillar Stationary Gas Engines.
- GE Jenbacher: Series 2, 3, 4 Fuel Class A and CAT. Series 6 (Version E&F)
- Fuel Class A and CAT

Data Sheet



Furnishing the information contained herein does not constitute a representation by Sigma Oil Industries Limited that any product of process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Sigma Oil Industries Limited or any third party. Sigma Oil Industries Limited assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions to use and application presented herein represent the best information available to us and are believed to be reliable. They should not however be considered as controlling suggestions and users urged to conduct confirmatory test to determine final suitability for their specific end usage. Sigma Oil Industries Limited warrants only that it's products meet the specification which is set for them and specially **DISCLAIMS ALL OTHER WARRANTIES** relating to the products and the application thereof **EXPRESS** or **IMPLIED** including but not limited to warranties of **MERCHANTABILITY** and **FITNESS**.

